



**Particulate Emissions and Heating
Efficiency Conforms to: ASTM E2618-13
and EPA M28WHH (using cordwood)**

Intertek

MANUFACTURER: Dectra Corporation
3425 33rd Avenue NE
Saint Anthony, MN 55418
612-326-1100

MODEL(S): WHS-2000V and WHS-2000H

Particulate Emissions Rate:	0.07 lbm/mmbtu output
	1.69 g/hr
Maximum Rate Output Capacity*:	200,000 Btu/hr
8-Hour Reload Output Capacity:	105,100 Btu/hr
8-Hour Average Efficiency:	76% (higher heating value)
	82% (lower heating value)
Annual Efficiency Rating:	74% (higher heating value)
	79% (lower heating value)
Fuel:	Seasoned Cordwood Only

* Based on reloading once every 4 hours with 24 inch long split white oak, with 22% moisture content.

IMPORTANT: THIS APPLIANCE IS INTENDED TO BURN SEASONED CORDWOOD FUEL ONLY. OPERATE IN ACCORDANCE WITH MANUFACTURER'S OPERATING INSTRUCTIONS ONLY. FAILURE TO OPERATE THIS APPLIANCE AS DIRECTED MAY RESULT IN VIOLATION OF AIR QUALITY REGULATIONS AND SUBJECT THE OPERATOR TO ENFORCEMENT ACTIONS INCLUDING FINES AND/OR REMOVAL ORDERS.